



Key Features & Benefits

- 4.3-inch, 480(w) x 272(h) pixel, 256k true colour, TFT active matrix, 450 (typ) cd/m2. LCD brightness is adjustable over a suitable range to accommodate different working conditions.
- USB Host Port on Front Face protected with Silicon Cover
- 4 x Integrated Lightbars. Each Lightbar has 1 central Green LED with 3 Amber LED's each side of the central LED.
- Ambient light sensor for Automatic brightness control
- 17 Logically placed backlit keys provide tactile feedback when activated, allowing operators to focus on the job and not the controls.
- 39-pin sealed military rated quick release tool-less connector
- Field upgradeable software via USB port.
- In-built buzzer (4 Volume settings) for operator feedback and warning

Options and Accessories

Product Specifications

Characteristics

Size:

Length:

200 mm

Width:

115 mm

Depth:

55.5 mm

Weight:

1.25 kg

Display:

4.3-inch, 480(w) x 272(h) pixel, 256k true colour, TFT active matrix, 450 (typ) cd/m2. LCD brightness is adjustable over a suitable range to accommodate different working conditions

General Housing Materials:

High pressure die cast aluminium

Environmental Characteristics

Temperature	
Operating:	-20 °C to +65 °C
Storage:	-40 °C to +85 °C
Humidity:	100% fully sealed, weatherproof
Sealing:	Fully Sealed to 3 PSI / IP68

Technical Specifications

Electrical Input Voltage:	9 V - 32 V
Supply Power	16 W (max) 8 W (typical)

Primary I/O Connector Styles

39 Pin I/O Connector

- A -
- B - Multi-state SWITCH INPUT 0
- C - Multi-state SWITCH INPUT 3
- D - BATT+
- E - SWITCH COMMON GND
- F - BATT-
- G -
- H - Multi-state SWITCH INPUT 4
- J - CAN0 LO
- K - CAN0 HI
- L - CAN1 HI
- M - CAN1 LO
- N - SIGNAL TXD2
- P - RS232-2 RXD2
- R - RS232-2 GND2
- S -
- T -
- U -
- V - Multi-state SWITCH INPUT 5
- W - BATT+
- X - Ign Switch
- Y - Multi-state SWITCH INPUT 1
- Z - Multi-state SWITCH INPUT 6

- a -
- b -
- c -
- d -
- e - CAN SHIELD
- f -
- g -
- h - RS232-0 RXD0
- i - RS232-0 TXD0
- j -
- k - Multi-state SWITCH INPUT 2
- m - BATT-
- n - AWAKE Gnd
- p - AWAKE Output
- q - SIGNAL GND0
- r -

Specifications subject to change without notice.

© 2011, Trimble Navigation Limited. All rights reserved. Trimble and the Globe & Triangle logo are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. Maxwell, and R-Track are trademarks of Trimble Navigation Limited. All other trademarks are the property of their respective owners. PN 022482-????



Trimble Heavy and Highway Division

10355 Westmoor Drive, Suite 100

Westminster, CO 80021

USA

800-538-7800 (Toll Free)

+1-937-245-5154 Phone

+1-937-233-9441 Fax

www.trimble.com

Trimble Authorized Distribution Partner